



NOTES:

- 1 IF PLATFORM SIZE IS REDUCED, THEN THE BLOCKING IS TO BE POSITIONED SUCH THAT IT IS CENTERED ON THE PLATFORM. (PLATFORM DEPTH / 2) + 2" = CENTERLINE OF RAIL BLOCKING OFF OF INSIDE FRONT WALL. (MIN. 28" DIMENSION)
- 2 CAR TO WALL (CTW) DIMENSION IS 3-1/2" MIN.
- 3 **HOISTWAY DOORS & FRAMES MUST BE INSTALLED TO COMPLY WITH THE AUTHORITY HAVING JURISDICTION REQUIREMENTS. THESE DIMENSIONS VARY. CONSULT YOUR RESIDENTIAL ELEVATORS SALES REPRESENTATIVE FOR DETAILS PRIOR TO CONSTRUCTION.**
- 4 HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)
- 5 CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL CAB DESIGN.
- 6 MINIMUM HINGE SIDE RETURN TO BE 8" TO ACCOMODATE GATE STACK.
- 7 MINIMUM HOISTWAY DIMENSION BASED ON 36" HOISTWAY LANDING DOOR

STANDARD HOISTWAY PLAN

NOTE: ALL DIMENSIONS ARE APPROXIMATE